



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ :

E05D 15/06, E06B 3/50

A2

(11) International Publication Number:

WO 95/23270

(43) International Publication Date:

31 August 1995 (31.08.95)

(21) International Application Number: PCT/CA95/00098

(22) International Filing Date: 23 February 1995 (23.02.95)

(30) Priority Data:

2,116,395	24 February 1994 (24.02.94)	CA
08/362,995	23 December 1994 (23.12.94)	US

(71) Applicant (for all designated States except US): 420820 ONTARIO LIMITED [CA/CA]; 500 Garyray Drive, Weston, Ontario M9L 1P8 (CA).

(72) Inventors; and

(75) Inventors/Applicants (for US only): DAVIES, Bob [CA/CA]; 4 Willowgate Drive, Markham, Ontario L3P 1G2 (CA). DAVIES, Sean [CA/CA]; 157 Moffat Avenue, Brampton, Ontario L6Y 4R8 (CA).

(74) Agents: HUGHES, Neil, H. et al.; Suite 200, 175 Commerce Valley Drive West, Thornhill, Ontario L3T 7P6 (CA).

(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).


Published

Without international search report and to be republished upon receipt of that report.

(54) Title: PARALLEL SUSPENSION SYSTEM

(57) Abstract

A closure assembly is provided including a track (15, 17) and a slidable and pivotable closure member (20). The closure member is engaged with the track proximate first and second pivots (55, 59) adjacent the pivotable end of the member, the first and second pivots being interconnected by a multiple segment shaft (50) (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment of the first and second pivots in a substantially parallel line for pivotally supporting the closure member so that it may be safely and securely pivoted away from the closure assembly.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgystan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

- 1 -

TITLE OF INVENTION

PARALLEL SUSPENSION SYSTEM

FIELD OF INVENTION

5 This invention relates to a mounting system for a
closure member in an assembly and improvements thereof which
allows the secure sliding and subsequent pivoting of the closure
member from a position parallel to the assembly, wherein sliding
of the closure member is allowed to a fully pivoted position. The
invention is preferably embodied in a window assembly but finds
10 application also in large pivoting windows and patio doors.

BACKGROUND OF THE INVENTION

Double hung windows are well known in the art. There
are a multiplicity of examples of such double hung windows which
incorporate window frames for the sliding of a window sash within
15 a jamb guide. Further there are many examples within the prior art
which allow for the sliding of a window sash within a frame within
the jamb channels thereof which further incorporate a carrier or
shoe attached to the window sash which allows for the pivoting of
the window sash away from the window frame.

20 A multiplicity of designs for sliding patio doors further
exist within the prior art. A typical patio door is made up of one
stationary framed main glass panel and one moveable framed main
glass panel sliding in a horizontal direction adjacent the stationary
panel and which does not typically pivot. The weight of the patio
25 door would require a substantial device in order to allow for the
secured pivoting thereof. Such hardware would further eliminate
or minimize the door sagging out of position and the need for
realignment of the doors when pivoted back to the closed position.
The pivoting of patio doors would be quite attractive and would
30 allow for the marketing of large French type doors in the industry.
No such doors exist within the market place at the present time.

Further within the prior art there is taught a tilt slider
and the hardware therefore as taught in United States Patent
4,888,915 issued December 26, 1989, United States Patent
35 5,168,665 and co-pending application 07/677,135 filed March 29,
1991 manufactured and distributed by Canadian Thermo Windows,
whose office is in Toronto, Canada. The manufacture of tilt and slide

SUBSTITUTE SHEET

- 2 -

5 windows, double hung windows, patio doors, and similar structures according to the teachings of the above mentioned three references obviated many of the prior art problems which will generally occur when any pivot block provided at the pivoting end of the window sash moves out of alignment in relation to the upper or lower pivot block adjacent the same lineal of the closure member. The only means for securing the sash of the window to the pivot block previously has been either a pin or strut. The continuing motion and sliding of the windows back and forth and the pivoting thereof causes the windows to misalign and sag under the weight of gravity especially when manufactured in a vertical tilt slider. United States Patent 4,888,915 and the above mentioned other references overcame this problem by an improved bracing system of the closure in the closure assembly by interconnecting the shoes in a carrier assembly and including with some embodiments a braking mechanism to ensure the window cannot slide when pivoted or a locking mechanism to ensure that the window cannot pivot when sliding in a track. In this way parallelism of the pivots whether stationary or in motion was assured by the required locking of the closure member. Such an assembly although much improved over the prior art has the drawback of requiring the user to latch and unlatch a number of levers to operate the window in its various modes of operation. This is primarily necessary to ensure that the pivots stay substantially parallel at all times so that for example the window is locked while pivoting thereby ensuring parallelism, or that the window is locked in the track while sliding also ensuring through the interconnection of the shoes a constant spacing and hence substantially parallel running as well. It is therefore desirable to eliminate as much of the consumer interaction with the window assembly as possible and make the operation as simple and fool proof as possible.

Nowhere within the prior art is such a simplified improved device provided which allows for the manufacture of heavier windows and doors in larger sections without the sagging of the window and having reliable operating pivots incorporated in the assembly which both allows for the pivoting and sliding of the

- 3 -

window by the user without the need for a multiplicity of user operated locks and latches.

Further in the manufacture of casement type windows there is found a large number of links and levers depending on the manufacturer of the window assembly. This renders the assembly costly to manufacture because of the assembly labour required. Further with protruding handles the window is prone to being damaged when shipped. One of the problems with known casement assemblies is that they are difficult to clean on the outside. US Patent 1,600,796 to Campbell addressed this concern. Further US Patent 1,341,366 endeavored to address this concern for casement windows. Final US Patent 5,289,656 attempted to improve on these previous structures. However the systems do not provide for ease of installation and variation in the window or door size which may be supported. Further the opening of the casement style windows provided to clean the outside of the window is insufficient to provide for all sizes of individuals and reaches.

It is therefore an object of this invention to overcome many of the deficiencies in the prior art stated above which allows for smooth and simple operation of a closure member which is capable of both sliding within a guide channel and tilting upon a pivot assembly thereof.

It is a further object of this invention to overcome many of the deficiencies in the prior art stated above which allows for smooth and simple operation and assembly of a casement style window which is capable of both pivoting to an open position, and allowing the pivoting end to slide within a guide channel to the opposite side of the frame within which the sash normally pivots for easy cleaning thereof.

It is a further object of the invention to provide casement windows of appropriate size and construction to replace existing double hung and/or tilt and slide windows.

It is a further object of the invention to provide a reliable carriage for use in relation to a guide channel disposed within a frame for a closure member and improvements therefore, whereby locking of the pivot when the closure member is rotated is unnecessary to maintain parallelism of the structure.

Further and other objects of this invention will become apparent to a man skilled in the art when considering the following summary of the invention and the more detailed description of the preferred embodiments illustrated herein.

5 SUMMARY OF THE INVENTION

According to one aspect of the invention, there is provided a closure assembly comprising a track and a slidable and pivotable closure member, the closure member being engaged with the track proximate first and second pivots adjacent the pivotable
10 end of the member, the first and second pivots being interconnected by a multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment of the first and second pivots in a substantially parallel line for pivotally supporting
15 the closure member so that it may be safely and securely pivoted away from the closure assembly, whereby the first and second interconnected pivots are adapted to remain engaged with the track while supporting the closure member both when it is pivoted away from the closure assembly and when it is slidable relative to the
20 track.

In one embodiment the closure assembly may further comprise a carrier traveling within said track having interconnected first and second portions, the first portion being engaged with the pivots of the closure member and the second portion being spaced
25 within the track from the first portion, the carrier to assist sliding movement and pivoting movement of the closure member preferably wherein the interconnecting means are adjustable in length.

Preferably the first portion further comprises an opening within which the first and second pivots are disposed to cooperate with the carrier portion. Preferably the first and second pivot portions may further comprise a rotatable pinion disposed therewith for facilitating the movement of the carrier relative to the track preferably in cooperation with a rack disposed with said
30 track. Preferably the closure member may further comprise latching means for latching the closure member to prevent pivoting thereof when the closure member is slidable relative to the track.
35

- 5 -

Preferably the closure member further comprises latching means for latching the closure member to prevent pivoting thereof when the closure member is slidable relative to the track wherein the latching means is a central locking member disposed
5 with the closure member.

According to another aspect of the invention, there is provided a pivoting and sliding closure assembly comprising:

i) an opening extending within a frame
ii) the frame having disposed therein or attached
10 thereto track portions extending in a substantially parallel direction to the extensions of said frame portions;

iii) at least one closure member slidable within said track portions and pivotable at least one end thereof and latchable in the track at the other end thereof;

15 iv) each track portions having disposed therein at least two pivot shoes adjacent the pivoting end of the closure member, each shoe being substantially compatibly shaped with the track and having a top and bottom, (preferably having rolling means disposed therein for assisting the movement of the pivot
20 shoe), each shoe adjacent the pivoting end of the closure member having disposed therein an opening extending from the top toward the bottom of the carrier wherein pivot means are disposed, said pivot means being interconnected by a multiple segment shaft (for example at least two portions) (for example telescoping) which
25 provides for accurate installation, retention, removal, adjustment and alignment of the first and second pivots in a substantially parallel line for pivotally supporting the closure member for safe and secure pivoting away from the closure assembly;

v) the closure member having latching means
30 provided therewith for latching the at least one closure member in relation to the track to prevent the closure member from pivoting upon its pivot means when the closure member remains slidable with said track

vi) the at least one closure member being braced
35 from sagging by the multiple segment shaft interconnecting the pivot means disposed with each track, the substantially parallel line of the pivots provided by the a multiple segment shaft preventing

- 6 -

the pivot means from sagging and/or disengaging from the relevant track when the at least one closure member is rotated to an open position and/or when it remains slidable within said track. Preferably the pivots may further comprise a rotatable pinion for
5 facilitating the movement of the carrier relative to the track preferably in cooperation with a rack disposed with said track. Preferably the closure member further comprises latching means for latching the closure member to prevent pivoting thereof when the closure member is slidable relative to the track wherein the
10 latching means is a central locking member disposed with the closure member.

Preferably said closure member may further comprise a window sash being a casement, double hung, or tilt and slide installation or, a door or a patio door.

15 According to another aspect of the invention, there is provided a pivoting and sliding closure assembly comprising:

- i) an opening extending within a peripheral frame said peripheral frame including a header portion, a sill portion and two vertically extending jamb portions;
- 20 ii) the sill and header portions or the two jamb portions having disposed therein or attached thereto track portions extending in a substantially parallel direction to the extensions of said peripheral frame portions;
- iii) at least one closure member slidable within said
25 track portions and pivotable at least one end thereof and latchable in the track at the other end thereof;
- iv) each track portions having disposed therein at least two pivot shoes adjacent the pivoting end of the closure member, each shoe being substantially compatibly shaped with the
30 track and having a top and bottom (preferably having rolling means disposed therein for assisting the movement of the pivot shoe), each shoe adjacent the pivoting end of the closure member having disposed therein an opening extending from the top toward the bottom of the carrier wherein pivot means are disposed, said pivot
35 means being interconnected by a multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment

- 7 -

and alignment of the pivots in a substantially parallel line for pivotally supporting the closure member for safe and secure pivoting away from the closure assembly;

v) the closure member having latching means provided therewith for latching the at least one closure member in relation to the track to prevent the closure member from pivoting upon its pivot means when the closure member remains slidable with said track;

vi) the at least one closure member being braced from sagging by the multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment interconnecting the pivot means disposed with each track, the substantially parallel line of the pivots provided by the multiple segment shaft preventing the closure member from sagging and/or disengaging from the relevant track when rotated to an open position or when it remains slidable within said track. In one embodiment said closure member is a window sash being a casement, double hung, or tilt and slide installation. In another embodiment said closure member is a door and preferably a patio door. Preferably the pivots may further comprise a rotatable pinion for facilitating the movement of the carrier relative to the track preferably in cooperation with a rack disposed with said track. Preferably the closure member may further comprise latching means for latching the closure member to prevent pivoting thereof when the closure member is slidable relative to the track wherein the latching means is a central locking member disposed with the closure member.

According to yet another aspect of the invention there is provided for use in a pivoting and sliding closure assembly, a closure member slidable within a guiding channel and pivotable therefrom, the closure member having a substantially rectangular frame having a top and bottom, and having engaged at its top and bottom at one end pivots for engaging a first and second shoe, and having disposed at the other end thereof proximate its top and bottom user accessible means for engaging the guiding channel (preferably wherein said user accessible means is a central lock);

- 8 -

said shoes being slidable in said guiding channel and comprising a substantially rectangular body having a top and bottom (preferably made from thermoplastic material) and preferably having disposed proximate the bottom thereof at least one roller or wheel), said shoes having disposed therewith pivot means (preferably the pivot means may further comprise a rotatable pinion for facilitating the movement of the carrier relative to the track preferably in cooperation with a rack disposed with said track) to engage with the shoes, said pivot means being interconnected by a multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment of the pivot means, each shoe having an opening for said pivot means, the opening extending from proximate the top towards the bottom of said shoe, whereby the closure member upon the pivot means pivoting away from the guide channel is braced from sagging by the a multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment and interconnecting of the pivot means disposed with each channel, the substantially parallel line of the pivots provided by the multiple segment shaft (for example at least two portions) (for example telescoping) preventing the closure member from sagging and/or disengaging from the relevant track when rotated to an open position or when it remains slidable within said track. In one embodiment said closure member is a window sash being a casement, double hung, or tilt and slide installation. In another embodiment said closure member is a door and preferably a patio door.

According to another aspect of the invention, there is provided a closure assembly comprising a track and a slidable and pivotable closure member, the closure member being engaged with the track proximate first and second pivots adjacent the pivotable end of the member, the first and second pivots being connected by a cable system connecting the upper and lower pivot shoes to move in and be maintained in substantially parallel positions at all times to retain and align the first and second pivots in a substantially parallel line for pivotally supporting the closure member so that it

- 9 -

may be safely and securely pivoted away from the closure assembly, whereby the first and second connected pivots are adapted to remain engaged with the track while supporting the closure member both when it is pivoted away from the closure assembly and when it is slidable relative to the track.

According to another aspect of the invention, there is provided hardware for a closure assembly having a track and a slidable and pivotable closure member, the closure member being engaged with the track proximate first and second pivots adjacent the pivotable end of the member, the hardware comprising the first and second pivots being interconnected by a multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment of the first and second pivots in a substantially parallel line for pivotally supporting the closure member so that it may be safely and securely pivoted away from the closure assembly, whereby the first and second interconnected pivots are adapted in use to remain engaged with the track while supporting the closure member both when it is pivoted away from the closure assembly and when it is slidable relative to the track.

According to another aspect of the invention, there is provided hardware for a closure assembly having a track and a slidable and pivotable closure member, the closure member being engaged with the track proximate first and second pivots adjacent the pivotable end of the member, the hardware comprising the first and second pivots being connected by a cable system connecting the upper and lower pivot shoes to move in and be maintained in substantially parallel positions at all times to retain and align the first and second pivots in a substantially parallel line for pivotally supporting the closure member so that it may be safely and securely pivoted away from the closure assembly, whereby the first and second connected pivots are adapted to remain engaged with the track while supporting the closure member both when it is pivoted away from the closure assembly and when it is slidable relative to the track.

According to yet another aspect of the invention there is provided a resiliently biased lock and handle which normally locks

- 10 -

the shaft of any of the aforementioned embodiments in operation until the handle is operated by a user wherein the lock is disengaged from the shaft and allows the shaft to rotate and when the handle is released again locks the shaft allowing for continuous
5 locking of the window at any position.

In an embodiment of the aforementioned invention in the preceding paragraphs when embodied in a tilt and slide or double hung window the inside rack portions provided within the track of the assembly, which extend the full width of the frame,
10 curve towards the stationary closed position for the window assembly and provide a closed window assembly in which both sashes are oriented in a straight line.

In an embodiment of the aforementioned invention in the preceding paragraphs when embodied in a tilt and slide,
15 casement or double hung window a retractable screen is provided disposed within the header or jamb of the assembly which accumulates on and pays out from a spring biased roll disposed within said header or jamb, the screen being retractable for egress or cleaning purposes, and available as desired by providing a detent
20 on the sill engageable with the screen when in its operatable position.

In an embodiment of the aforementioned invention in the preceding paragraphs when embodied in a casement window a link having two ends is fastened at one end proximate the center of
25 the bottom of the window sash and proximate the other end adjacent the end of the sill of the window frame to allow for full operation of the casement window from a fully closed to a fully open position and the movement of the pivoting end of the window towards the opposite end so as to allow full access to the outside of
30 the window and the easy cleaning thereof. In another embodiment the link is removable to allow total reversing of the window for cleaning and/or removal purposes.

In another embodiment of the invention the rack disposed with the track is made from aluminum and formed in
35 three separate steps so as to minimize the amount of vertical creeping of the rack when formed. The rack also acts as a liner to

- 11 -

distribute the load of the sash and minimize distortion of the vinyl track.

According to the following improvements of the invention reference is made to the previous structures described substantially in the first eleven paragraphs of this disclosure. Whenever reference is made below to the structures or invention of the "above mentioned paragraphs" or "described above" or the like its is intended to refer the reader primarily to the paragraphs of the improvements to the summary of invention and the structures defined therein immediately following this paragraph.

According to yet another aspect of the invention there is provided a closure assembly comprising a track and a slidable and pivotable closure member, the closure member being engaged with the track proximate first and second pivots adjacent the pivotable end of the member, the first and second pivots being interconnected by a multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment of the first and second pivots in a substantially parallel line for pivotally supporting the closure member so that it may be safely and securely pivoted away from the closure assembly, whereby the first and second interconnected pivots are adapted to remain engaged with the track while supporting the closure member both when it is pivoted away from the closure assembly and when it is slidable relative to the track. Preferably the first and second pivot portions further comprise a rotatable pinion disposed therewith for facilitating the movement of the carrier relative to the track. In a preferred embodiment wherein the rotatable pinion moves in cooperation with a rack disposed with said track. The closure assembly may further comprise a window sash being a casement, double hung, or tilt and slide installation or, a door or a patio door.

According to yet another aspect of the invention there is provided a pivoting and sliding closure assembly comprising:

- i) an opening extending within a frame
- ii) the frame having disposed therein or attached thereto a first and second track portion extending in a substantially parallel direction to the extensions of said frame portions;

- 12 -

iii) at least one closure member slidable within said track portions and pivotable at least one end thereof and latchable in the tracks at the other end thereof;

iv) each track portions having disposed therein a pivot shoe adjacent the pivoting end of the closure member, said shoe being substantially compatibly shaped with the track and having a top and bottom, (preferably having rolling means disposed therein for assisting the movement of the pivot shoe in the track), the shoe having disposed therein an opening extending from the top toward the bottom of the shoe wherein pivot means are disposed, said pivot means of said shoe disposed with said first track portion being interconnected with the pivot means of the shoe in the second track portion by a multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment of the first and second pivots in a substantially parallel line for pivotally supporting the closure member for safe and secure pivoting away from the closure assembly;

v) the closure member having latching means provided therewith for latching the at least one closure member in relation to the track to prevent the closure member from pivoting upon its pivot means when the closure member remains slidable with said track

vi) the at least one closure member being braced from sagging by the multiple segment shaft interconnecting the pivots disposed with the pivot shoe of each track, the substantially parallel line of the pivots provided by the a multiple segment shaft preventing the pivots from sagging and/or disengaging from the relevant track when the at least one closure member is rotated to an open position and/or when it remains slidable within said track. Preferably the pivots further comprise a rotatable pinion for facilitating the movement of the shoe or carrier relative to the track. In one embodiment the pinion moves in cooperation with a rack disposed with said track. The closure assembly may further comprise a window sash being a casement, double hung, or tilt and slide installation or, a door or a patio door.

- 13 -

According to still yet another embodiment of the invention there is provided a pivoting and sliding closure assembly comprising:

- 5 i) an opening extending within a peripheral frame said peripheral frame including a header portion, a sill portion and two vertically extending jamb portions;
- 10 ii) the sill and header portions or the two jamb portions having disposed therein or attached thereto first and second track portions extending in a substantially parallel direction to the extensions of said peripheral frame portions;
- 15 iii) at least one closure member slidable within said track portions and pivotable at least one end thereof and latchable in the track at the other end thereof;
- 20 iv) each track portions having disposed therein a pivot shoes adjacent the pivoting end of the closure member, said shoe being substantially compatibly shaped with the track and having a top and bottom, (preferably having rolling means disposed therein for assisting the movement of the pivot shoe), said shoe having disposed therein an opening extending from the top toward the bottom of the carrier wherein pivot means are disposed, said pivot means for said shoes disposed within said first and second tracks being interconnected by a multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment of the pivots in a substantially parallel line for pivotally supporting the closure member for safe and secure pivoting away from the closure assembly;
- 25 v) the closure member having latching means provided therewith for latching the at least one closure member in relation to the track to prevent the closure member from pivoting upon its pivot means when the closure member remains slidable with said track;
- 30 vi) the at least one closure member being braced from sagging by the multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment interconnecting the pivot means disposed with each track, the
- 35

substantially parallel line of the pivots provided by the multiple segment shaft preventing the closure member from sagging and/or disengaging from the relevant track when rotated to an open position or when it remains slidable within said track. In one
5 embodiment said closure member is a window sash being a casement installation. In another embodiment the closure member is a window sash being a double hung, or tilt and slide installation. Preferably the pivots further comprise a rotatable pinion for facilitating the movement of the carrier relative to the track, and in
10 one embodiment wherein said pinions move in cooperation with a rack disposed with said track.

According to yet another aspect of the invention there is provided for use in a pivoting and sliding closure assembly, a closure member slidable within a guiding channel and pivotable
15 therefrom, the closure member having a substantially rectangular frame having a top and bottom, and having engaged at its top and bottom at one end pivots for engaging a first and second shoe, and having disposed at the other end thereof proximate its top and bottom user accessible means for engaging the guiding channel
20 (preferably wherein said user accessible means is a central lock);

said shoes being slidable in said guiding channel and comprising a substantially rectangular body having a top and bottom (preferably made from thermoplastic material) and preferably having disposed proximate the bottom thereof at least
25 one roller or wheel), said shoes having disposed therewith pivot means (preferably the pivot means may further comprise a rotatable pinion for facilitating the movement of the shoe relative to a track provided with said guiding channel and preferably in cooperation with a rack disposed with said track) to engage with the
30 shoes, said pivot means being interconnected by a multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment of the pivot means, each shoe having an opening for said pivot means, the opening extending from
35 proximate the top towards the bottom of said shoe, whereby the closure member upon the pivot means pivoting away from the guide channel is braced from sagging by the a multiple segment

- 15 -

shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment and interconnecting of the pivot means disposed with each channel, the substantially parallel line of the
5 pivots provided by the multiple segment shaft (for example at least two portions) (for example telescoping) preventing the closure member from sagging and/or disengaging from the relevant track when rotated to an open position or when it remains slidable within said track. In one embodiment the pivot means further comprises a
10 rotatable pinion for facilitating the movement of the carrier relative to the track and preferably wherein said pinion moves in cooperation with a rack disposed with said track.

According to yet another aspect of the invention there is provided hardware for a closure assembly having a track and a
15 slidable and pivotable closure member, the closure member being engaged with the track proximate first and second pivots adjacent the pivotable end of the member, the hardware comprising the first and second pivots being interconnected by a multiple segment shaft (for example at least two portions) (for example telescoping) which
20 provides for accurate installation, retention, removal, adjustment and alignment of the first and second pivots in a substantially parallel line for pivotally supporting the closure member so that it may be safely and securely pivoted away from the closure assembly, whereby the first and second interconnected pivots are
25 adapted in use to remain engaged with the track while supporting the closure member both when it is pivoted away from the closure assembly and when it is slidable relative to the track.

Preferably the hardware may be embodied in a casement window wherein a link having two ends is fastened at one
30 end proximate the center of the bottom of the window sash and proximate the other end adjacent the end of the sill of the window frame to allow for full operation of the casement window from a fully closed to a fully open position and the movement of the pivoting end of the window towards the opposite end so as to allow
35 full access to the outside of the window and the easy cleaning thereof. In another embodiment the link is removable to allow total reversing of the window for cleaning and/or removal purposes.

- 16 -

According to another aspect of the invention the inventions described in the last six paragraphs may be embodied in a tilt and slide, casement or double hung window wherein a retractable screen is provided disposed within the jamb of the assembly which accumulates on and pays out from a spring biased roll disposed within said jamb, the screen being retractable for egress or cleaning purposes, and available as desired by providing a detent on the sill engageable with the screen when in its operatable position.

According to another aspect of the invention the inventions described in the last six paragraphs the rack disposed with the track is made from aluminum and formed in three separate steps so as to minimize the amount of vertical creeping of the rack when formed and preferably wherein the rack also acts as a liner to distribute the load of the sash and minimize distortion of the vinyl track.

In a preferred embodiment of the invention described above, the frame portions, for example the headers, vertical jambs or sills are formed separately from the track. The track includes an integral rack portion proximate one side thereof, said rack portion including a plurality of teeth extending substantially from end to end of said track, and for engagement with the rotatable pinion of said carrier which facilitates the movement of the carrier relative to the track. The track is fixed in position relative to the headers, sills and/or jambs by the provision of two supplementary portions. The first supplementary portion is a block which has two ends, a top and a bottom, the block having disposed in use proximate the top thereof opening to receive fasteners which opening extend to the bottom of the block. The fasteners are for engagement with the frame portion and preferably the wooden base portions of the frame and are provided to lock the first block in position in relation to the end of the track remote the pivoting end of the closure member, and thereby fixing the track in position. The first block has disposed therewith an adjuster moveable in relation to said block in a direction extending towards said track and preferably rotatable, said adjuster being engageable with a second supplementary portion, and preferably a nut portion having track

- 17 -

shaped abutting portions proximate one side thereof, and for engagement with said track. The second portion has elements provided therewith which are engageable with said adjuster and said track, said adjuster being moveable in position to move the track abutting portions in relation to the rack provided with the track, wherein movement of said adjuster will move said second portion and preferably said nut in relation to said track and said rack in a direction toward and away from the block thereby adjusting the position of said track in relation to said frame portions and thereat fixing said rack in position. The main advantage of providing such an adjustment for the track is to establish and allow for the alignment or adjustment of the closure member and to maintain the parallelism of the carrier in relation to for example both a bottom and a top track in the case of a tilt and slide or casement window, or the left and right side in the case of a double hung widow, so that the pivots remain substantially parallel and square to one another. Aluminum is preferably used for the track since it is able to take the weight of the window more readily than vinyl or other plastic material. The track may be formed from the previously mentioned three separate steps so as to minimize the amount of vertical creeping of the rack when formed. In a preferred embodiment, the adjuster is a rotatable cap screw preferably having an opening therein for an allen key, and which is contained within an opening proximate one end of the first block remote the track and wherein said cap screw is threaded into the second block or preferred nut, wherein rotation of the screw in relation to the fixed block, for example by an allen key, will cause the second block or preferred nut to move fore and aft in relation to the track and provide for a final adjustment or readjustment of the track in relation to the carrier in both the top and bottom or side tracks of the window system depending on what window system is used. Preferably the block is manufactured from aluminum, and the adjuster nut is manufactured from Delrin(TM). In another embodiment, the block and nut are manufactured from fiber filled nylon. In a preferred embodiment of the invention, both the first block and second nut further comprise a detent, for example a right angled triangle notch proximate the top thereof for engagement

- 18 -

with a lock in use for a pivoting window, the lock being compatible with the detent. The blocks therefore provide a reinforced portion of the window frame against which the lock may abut in use. Otherwise the lock would engage only a vinyl flange of the sill or header for example, and the window load may in time tear or distort said flange to render it useless.

In another a preferred embodiment of the invention, the rack formed integral with the track further comprises an upstanding flange disposed proximate one side of the track wherein the rack is disposed having a plurality of teeth for engagement with the pinion gear of the carrier. Preferably the rack is formed by a three-step process to minimize the amount of vertical creeping of the preferred aluminum material. Preferably a pivot shoe is provided for engagement with said rack and track further comprising a carrier having a top and a bottom, the carrier having disposed proximate the bottom thereof means, and preferably slots, for retaining rollers, and the rollers in use thereof for providing the smooth movement of the carrier within the track, preferably the rollers being engaged with a predetermined channel formed in said track, said carrier also having an opening disposed proximate the top thereof wherein a pivot gear is disposed, said pivot gear having a top and a bottom and having disposed proximate the top thereof a pivot engaging portion for engaging the pivot of a closure member such as a window sash, said pivot gear having disposed proximate the bottom thereof an anti-thrusting wheel portion for engagement with a shoulder provided proximate each side of the track channel, for example to engage the shoulder of the channel as a result of thrust which may be caused by the wind load on the closure member and the normal thrust caused by meshing of gears, the anti-thrusting wheel preferably being of a predetermined diameter of a dimension less than the channel of the track so as to minimize drag in the track, said pivot gear having disposed intermediate said pivot engaging portion and said anti-thrust wheel portion a pinion gear portion for engaging the rack, wherein the previously described closure member and specifically the pivots thereof engages with the carrier portion, wherein movement of said carrier portion will affect rotation of said pinion in relation to said track

- 19 -

and the smooth movement of the carrier along the track maintaining the parallelism, of said upper and lower pinions for the case of both a tilt and slide and casement window, and said left and right pinions in the case of double hung windows. Preferably said carrier portion is made from Delrin(TM), and said pivot gear portion is made from nylon. The anti-thrust wheel portion is provided to engage the shoulders provided adjacent the recess of the track to accommodate any thrusting of the pinion which might occur, due to wind loading or the like and the rotation of the gears, and to maintain the pinion substantially central in relation to the carrier at all times. The rollers provided proximate the bottom of said carrier are to ensure smooth movement of the carrier in relation to the track. Preferably the rollers are made from metal.

In another preferred embodiment of the invention, the vinyl profile forming the closure member (for example a sash profile) may further comprise a cover disposed on the side of the profile opposite the glass, which cover extends substantially along the length of the profile and which has disposed proximate the sides thereof two flanges for locking engagement underneath flanges provided with the profile, said profile further including a space defined within said profile enclosed by said plastic cover, preferably said space containing in use a closed cell foam or the like, for example a closed cell caulking foam, which is compressible, said plastic cover having disposed proximate the bottom thereof intermediate said flanges spring-loaded members, for example fingers, engageable with said foam, and preferably when installed slightly loading said foam to create a spring biased resistance of the foam against the cover further locking the cover in position with the profile. Preferably the cover is made from thermoplastic or thermoset material and when installed extends down from said profile toward the space defined within said track portion between the flanges thereof. The cover provides a locking flexible seal throughout the length of the closure member with the exception of the area adjacent the carrier portion located proximate the pivoting end of said closure member. In various embodiments of the invention, the cover may be embodied with a casement window, a tilt and slide window and a double-hung window. The use of a

- 20 -

closed cell foam such as caulking foam or the like in the space within the profile provides resilience and strength to the cover along the length of the profile and therefore allows for the foam and cover together to provide a surface upon which the closure member
5 may travel while the carrier moves in the track. Also, the cover behaves as a seal for the profile and in use indirectly for the track to keep dust and other undesirable elements out of the track and out of the profile, and assists to prevent passing cold air.

According to yet another aspect of the invention and in a
10 preferred embodiment thereof, there is provided a release mechanism for locking a closure member from pivoting movement in a closure assembly, the closure member being carried by the carrier described in the above paragraphs, said release mechanism further comprising operating means disposed with the closure
15 member, and preferably with the window sash elements, said operating means may be provided intermediate the lockable ends of the closure member, and accessible to the user. For example, when the closure member is provided within a tilt and slide window, the operating means will generally be disposed in a vertical plane
20 provided with a vertical sash element so that the operating member when operated will cause the locking and unlocking of the tilt and slide window and allow free movement thereof. When the operating means is provided in a double-hung window, the operating means may be a handle disposed in a horizontal plane
25 and being operable by the user to and from a locked and released position to allow movement of the double-hung window, for example, pivoting thereof to access the exterior pane surface and provide cleaning thereof. In another embodiment when the closure member is a casement window sash, the operating member may be
30 disposed in a substantially vertical direction and is operable by the user to and from a locked and unlocked position, the operating means being user operable to and from a first locked position and a second unlocked position. In all cases, bi-directional locking means are provided with the sash profile and being moveable by the
35 operation of said operating means to cause locking portions engaged with said bi-directional locking means to move in and out of engagement with track portions (and in one embodiment the

- 21 -

previously described block and nut portions) disposed proximate at least two opposed locations of said closure assembly, and when the window is a casement window further locking action resulting from the engagement of a third portion in and out of locking engagement

5 with a locking detent provided adjacent the jamb wherein the window sash is contained. The operation of the operating means in a first direction causes the locking portion to move out of engagement with, the track portions or the detent provided with the track portion, and when a casement window is in use, the

10 locking detent adjacent to the jamb, to therefore allow pivoting movement of the closure member. Movement of the operating means in the second direction causes the locking portions to move into engagement with the track portions or the detent provided with the track portion and therefore prevent the pivoting

15 movement of the closure member. In a preferred embodiment, the release mechanism for locking a closure member includes a handle portion which has provided proximate one end thereof a handle and proximate the other end thereof a pinion, said pinion being engageable with a rack portion proximate one side thereof and a

20 second rack portion proximate the other side thereof, said rack portions being engaged with locking portions which extend to the track or detent provided with the track in use to latch and unlatch the closure assembly, for example the window. When a casement window embodies the release mechanism, the pinion portion also

25 engages one of the rack portions which further engages a second pinion rotatable by the motion of the second rack, the second pinion being engageable with a latch portion including a pinion sector provided therewith, causing the rotation of the latch portion into and out of engagement with a detent portion provided proximate

30 the jamb of a casement window assembly, said single handle therefore operating both the locks proximate the track portion and when a casement window is used the lock proximate the jamb portion. Applicant refers the reader to United States Patent Application 08/171,750 filed December 22, 1993, by the proprietor

35 of the Assignee for this Patent Application, specifically referring to Figure 33 and a description of a bi-directional operating or release mechanism, the contents thereof which is hereby incorporated by

- 22 -

reference, in relation to the structure and operation of the bi-directional release mechanism.

According to yet another aspect of the invention of the casement window assembly described above, there is provided a casement window assembly further comprising a jamb portion located proximate the pivoting end of the casement window preferably said window including a clip in flexible cover for the sash, said jamb portion including a pocket portion extending substantially towards the casement window sash and providing a pocket for the pivoting end of the casement window wherein said carrier is disposed in use, thereby providing a recess or pocket within which the closed casement window proximate the pivoting end thereof is located and when a cover is provided with the sash to snap fit into to improve the seal and weatherproofing of the casement window, said pinion upon pivoting of the casement window causing the rotation of said gears and the sliding motion of the pivoting end of the window away from the jamb pocket thereof to prevent binding of the pivoting end with the pocket extending with the jamb portion, thereby providing the sealing improvements to the casement window, wherein when the casement window is moved to the closed position, the pivoting end will move back into the pocket provided.

According to yet another aspect of the invention, there is provided a conversion kit for a frame opening to convert a, a double-hung window or a tilt and slide window to a casement window assembly, said conversion kit comprising framing portions for containing track portions engageable with the framing portions of the window frame section (for example header and sill, or two vertical jamb members), said track portion, preferably being made from aluminum, and including a rack portion proximate at least one side thereof, a casement window sash having a carrier and interconnecting pivot assembly provided therewith substantially as described above, and for insertion and operation with respect to the track portions of the frame, wherein said casement window fully fills the space occupied by the previously installed double-hung or tilt and slide window, and the jamb, sill, and header portions are installed in the space provided. Typically, casement windows

- 23 -

known today are narrow and of standard sizes. The known prior art hardware therefore provided prohibits the installation of a casement window where double hung or tilt and slide windows were previously installed. The present invention however opens up the possibility of changing window types as the consumer desires. Therefore, the existing window assembly is stripped out down to the wooden frame section. The installer installs the vinyl header sill and jamb section to the wooden frame chambers. The tracks are then installed, and preferably using the block and nut portions previously described, the block portion being screwed into the vinyl sill and header and the wooden frame members. The hardware with the carriers and interconnected pivots are then installed with the sash and squared in position. The window sash includes in the preferred embodiment the central locking handle and racks and pinions contained in the sash adjacent the opening end and contains the interconnecting shaft for the pivots. The casement window therefore replaces the previous window installation. Preferably a screen is provided with the vertical jamb on the inside of the casement window which can be extended and retracted in position to cover a window opening when the casement is open and to retract when the window is closed.

According to yet another aspect of the invention, there is provided a method of assembling a window sash, said window sash being used with a casement, tilt and slide or double-hung window and being interchangeable and of standard construction with respect to the various window sashes required, said method comprising:

- (1) forming the sash element according to the standard profile, said standard profile comprising a generally rectangular "I" shaped member having a center reinforcement comprising an inner and an outer wall and a hollow therebetween and having extending from the ends of these inner and outer walls proximate both the top and bottom thereof substantially "I" shaped members extending substantially horizontally in profile extending along the length of the sash element also having inner and outer walls and a hollow

5 therebetween, the sash element having provided proximate one end thereof flanges extending inwardly toward one another for receiving a dust cover or auxiliary member fastening thereto and having located proximate the other end thereof a glass engaging recess, the cover or auxiliary member being fastened to the sash profile and being variable from window style to window style,

10 (2) inserting the glass within the glass receiving portion of the sash elements and,

15 (3) connecting said sash elements with interior corner connectors having a quick fastening feature which are inserted within the central opening of the sash profiles provided and provide a one-way friction fit for connecting the corners proximate the interior of the sash element ,

wherein said sash may be used for a tilt and slide window, double-hung window, or casement windows.

20 A method therefore of assembling the window is provided wherein, the sash components are assembled around a typical sealed double pane window glass by the quick fastening feature of the corner locking portions which are inserted within the opening of the sash profiles provided and provide one-way friction fit. The closed cell caulking is therefore inserted within the top and
25 bottom of the sash assembled and these portions are covered by track covers by the compression of the closed cell foam and the engagement of the tabs of the track cover with the tabs of the sash profile. The hardware is then installed along the vertical portions of the sash within the openings thereof opposite the glass which is
30 then covered by a sash cover portion provided. The hardware located proximate the pivoting end is therefore installed on the carrier portions and inserted within the track portion within the sill and header, for example of a window assembly. The window is therefore closed in position with the sash covers or track covers
35 located proximate the sill and header snapping into the frame and closing any path for air to enter the window and pass the primary seals provided . The track covers also provide blockage of light, air

- 25 -

and the friction fit of the sash into the track portions. By providing a track cover along the track remote the pivoting end of the window, this track cover may be used as support as well for the window assembly.

5 According to another aspect of the invention of the casement window described above, the casement window may further comprise a straight line window frame and assembly having a center mullion wherein casement windows are disposed on each side of the mullion with the operating portions including the carrier
10 and interconnected pivot assembly and shafts thereof described above, thereby providing a double-casement window, wherein said casement windows pivot in substantially opposite directions, and provide a straight-line window when in the closed position. According to yet another aspect of the invention, there is provided a
15 cover for a tilt and slide window track, the track comprising a first half and a second half interconnected to provide a continuous track for the window, the first half being disposed below the closed window, and the second half being provided as a continuation of the first half, the second half including the track cover portion which
20 clips into position to engage the flange portions of the sill of the window and thereby provide support for the window as it glides along the second half of the track.

BRIEF DESCRIPTION OF THE DRAWINGS

25 Figure 1 is a schematic perspective view of a tilt and slide window, wherein said windows move in a horizontal direction, illustrated in a preferred embodiment of the invention.

 Figures 1A and 1B are partial schematic perspective views of casement style windows embodying the invention and depicting the motion thereof and illustrated in a preferred
30 embodiment of the invention.

 Figures 1C is a partial schematic perspective view of straight line windows embodying the invention and depicting the motion thereof and illustrated in a preferred embodiment of the invention.

35 Figures 1D is a partial cutaway view of the casement style windows of Figure 1A depicting a rollaway screen thereof and illustrated in a preferred embodiment of the invention.

- 26 -

Figure 2 is a front view of the window of Figure 1.

Figure 2a is a top view of the window of Figure 1.

Figure 2b is a end view of the window of Figure 1.

Figure 3 is a double hung window assembly utilizing
5 hardware similar to that of Figure 1 and illustrated in a preferred
embodiment of the invention.

Figure 4 is a perspective illustration of the hardware
only for a double hung window of Figure 3.

Figure 5 is an exploded perspective view of the
10 components of the hardware of Figure 4 to be installed in a double
hung window assembly.

Figure 6 is a carrier design illustrated in a preferred
embodiment of the invention which allows for ease of removal of a
window from a window assembly and illustrated in an exploded
15 perspective view.

Figure 7 is an assembled view of the components of
Figure 6.

Figure 8 is a tilt and slide window assembly primarily
for the hardware therefore and illustrated in an alternative
20 embodiment of the invention.

Figure 9 is a schematic view of the movement of the
shoes of Figure 8 illustrated in alternative of the invention.

Figure 10 is a perspective illustration of a pulley
arrangement installed at the corners of the window assembly of
25 Figure 8 and illustrated in alternative embodiment of the invention.

Figure 11 is a close-up perspective view of a locking
mechanism for the shaft assembly 30 illustrated in a preferred
embodiment of the invention.

Figure 12 is an end view of the locking mechanism of
30 Figure 11 illustrated in a preferred embodiment of the invention.

Figure 13 is an end view of a locking block assembly
illustrated in a preferred embodiment of the invention.

Figure 13A is an end view of the track profile used in
conjunction with the lock block assembly of Figure 13 and
35 illustrated in a preferred embodiment of the invention.

- 27 -

Figure 13B is a top schematic view of the lock block assembly of Figure 13 shown engaging the rack portion of the track and illustrated in a preferred embodiment of the invention.

5 Figure 13C is a side cross-sectional view of the adjusting cap screw used to adjust the track within the sill or header or jamb portions and illustrated in a preferred embodiment of the invention.

Figure 14 is a top view of the carrier for the shaft assembly of Figure 17 and illustrated in a preferred embodiment of the invention.

10 Figure 14A is a cross-sectional view through the diameter of the opening 35b of Figure 14 illustrated in a preferred embodiment of the invention.

Figure 15 is an top end view of the sash portions for a tilt and slide window assembly from the opening end of the window and illustrated in a preferred embodiment of the invention.

Figure 15A is a close up view of the section of the assembly of Figure 15 where the sash abuts with the sill and illustrated in a preferred embodiment of the invention.

20 Figure 16 is a schematic end view of a central locking system best seen in Figure 17 and illustrated in a preferred embodiment of the invention.

Figure 16A is an end view of the central locking system of Figure 16.

25 Figure 16B specifically illustrates the latching plate and latch of the central locking system and illustrated in a preferred embodiment of the invention.

Figure 17 is an exploded perspective view of a window sash for a tilt and slide or casement window illustrated in a preferred embodiment of the invention.

30 Figure 18 is an exploded perspective view of the header, sill and jamb portions of the window assembly illustrating the track and its positioning in relation to the sill and header and illustrated in a preferred embodiment of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

35 Referring now to Figure 1, 2 through 2b there is illustrated a tilt and slide window assembly. Therefore the assembly 5 includes an outer frame portion 10 which is normally

hung within an opening established in a building (not shown). Normally nailing flanges are provided for this purpose attached to the outer frame 10. The frame 10 includes top portions 17 and bottom portions 16 having tracks disposed therein, as best seen in relation to Figure 2. Within the tracks are contained a pivot assembly which will be hereinafter described. Primarily the pivot assembly includes a pinion 35 and carriers 38 and 37 interconnected by interconnecting portions 32 and 31 making up an interconnecting member 30. The pinions move as the window 20 is slide in the track portion by the movement of the pinion 35 with respect to the rack 18 or 19 respectively. In this way the pinions 35 being interconnected remain parallel at all times in their motion along the track within which the rack 19 or 18 is disposed. The hardware is shown in normal view while the window assembly is shown in dotted lines, to illustrate the essence of the assembly.

Referring now to Figure 2 there is illustrated the window of Figure 1, wherein a window 20 and 40 is slidable within a track 15 and 17 upon a shoe 39. The lower shoe 39 also is connected to a secondary shoe 39a for carrying the window which includes rollers 39b, 39a1 and 39b2 on the bottoms thereof respectively for ease of movement within track 17. The pinion 35 rests within the shoe 39 as will be described hereinafter. The arrangement of the interconnecting portion 30 will also be described hereinafter. Window 40 therefore has its own interconnected system as can be best seen in relation to Figures 2a and 2b.

Referring now to Figure 2a there is illustrated the sash elements 20 and 40 and the rack portions 19 and 19a which accommodate the motion of the pinion 35 along a full length of the track, as best in Figure 2b.

Referring to Figures 1, 2 to 2b clearly the track portion 17 and 15 cooperate with the rack portions 19 and 19a to provide for the pinion 35 and its motion when the window remain slidable within the track. By interconnecting the two pinion portions and hence the two pivot shoes, by interconnecting means 30, the shoes remain in a substantially parallel position in relation to one another at all times. This overcomes the problem described in the

- 29 -

background of the prior art. By remaining parallel it is almost impossible for the window therefore to come out of the track when the window is pivoted to be cleaned and therefore is no longer necessary to provide braking portions as in previously described inventions of Canadian Thermo Windows, as referred to in the background of the invention.

Referring to Figures 1A and 1B there is illustrated a casement style window having similar components to that found in relation to Figure 1 with the exception of only one sash being provided being secured on shaft assembly 30 including portions 31 and 32. A link L is provided secured proximate ends L1 adjacent the center of the sash 21 proximate the bottom thereof and adjacent the track 18 adjacent the opening end of the window sash 21. By positioning the sash in this manner a full range of pivoting motion is available. If the link end L1 is removable than the window sash may be moved totally to the opposite end remote the pivoting end 21b on shoe 39. As with the case of the tilt and slide window a shoe 39 containing a pinion is provided. The pinion is connected to the shaft 30 and engages the rack 18 as it moves along the window sill and header in parallel arrangement between the upper and lower pivots maintained in parallel by the shaft 30. In this manner the casement style window may be pivoted as normal to an open position, and the pivoting end may be moved to the other end of the window frame away from side 21b to allow ease of cleaning. By supplying the hardware described without a casement sash the casement window may be assembled without the need for expensive pivots and linkages and without a great deal of assembly labour. As best seen in Figure 1D for the casement style window in particular a rollaway screen S may be provided which is housed in jamb 17a as illustrated. The screen S pulls across to engage detent D1 with detent D2 in jamb 16a, whereat it may be locked. This allows a user to clean the glass of sash 21 on the inside without removing the screen.

Referring to Figure 1C there is illustrated a tilt and slide type window similar to figure 1 with the exception that when closed the window sashes will be oriented in a straight parallel line with one another. In order for this to happen the rack provided 18

- 30 -

includes a portion 18a made from fiber filled plastic or the like and joined at seam 18c to an aluminum track 18b. The sash 21 is therefore moveable as previously described on carrier 39 and rollers 39a as urged by pinion 35 until the pinion reaches the curved portion of the track 18 a wherein the assembly 30 will move along the curve to the terminus of the track 18t. The sash portion 21a will then lock in behind the edge of the sash contained in track 18' and be lockable at that position. The sash 21'(not shown) resides on assembly 30' in track 18'. As pinion 35' moves within the limits of rack 18' the sash 21 cannot adopt a parallel position unless sash 21' is in its fully closed position. Only then can the end 21a adopt its fully closed position butting up against the sash 21' at the end opposite the carrier assembly 30 and 39.

Referring to Figure 3 there is illustrated a double hung window assembly embodying the preferred embodiment of the hardware making up the invention substantially equal to that which is disclosed in Figure 1, with the exception that a coil spring 31a is provided around the connector portion 31 of the interconnecting portion 30. By providing the interconnecting portion 31 with a spring 31a it will no longer be necessary in a double hung window assembly to provide a sash balance, as the spring 31a is pre-loaded to provide the necessary tension, much the same as a spring which is used in a garage door. In this example as a garage door goes up and down the spring is compressed and tensioned depending on the motion of the door and therefore provides for the return motion of the window assembly. Within the window assembly sashes 20 and 40 shown in ghost line are moveable with hardware substantially made up of a pivot or pinion 35 moving on a rack 18 and 19 respectively and being interconnected by the interconnecting portion 30.

Referring to Figures 4 and 5 there is illustrated the hardware which is installed within the double hung window assembly of Figure 3. Pinions 35 therefore are provided, which seat within the carriers or shoes 39. The pinion includes a shaped opening 35a which is compatible with the bar stock 34c and 32a proximate the ends thereof. The pinion therefore will ride on the rack 18 and 19 within shoe 39. Opposed supplementary portion 37

- 31 -

is provided to oppose the shoe 39 as it rides in the track. Therefore, referring to Figure 2b the portion 37 and 38 may be readily seen. A combined ratchet and pawl assembly is provided with portion 37 or at least connected therewith. The pawl assembly 37c is resilient
5 biased through the opening 37d of member 37 so as to release the ratchet 34b of shaft 34 when the window is to be removed from the assembly. Proximate the other end of the hardware there is provided a backing member 38 in a unique shaft extension 33 which includes portions 33b, 33d, 33c and 33a wherein the shaft
10 end 32a extends through. A locking nut 33e is provided to lock the entire hardware together and to allow for ease of separation thereof. An adjustable connector 31b is provided proximate the other end which allows for adjustment with regard to the length of section 32 of the shaft so as to allow variation in the sizes of the
15 assembly supported. Portions 31, 31b, 32, and 33 makeup the shaft assembly which allows for ease of installation, adjustment, alignment and removal of the sash assembly. Also the hardware therefore described provides for the interconnection of the pivot shoes proximate their sides and provides for parallel motion of the
20 pivot shoes at all times thereby illuminating the need to lock the pivot shoes in the track assembly.

Referring to Figure 6 there is a description of a different shoe construction which is useful when a window is removed, since the carrier will be locked in position when the window is removed
25 for maintenance or for cleaning. Therefore the shoe 39 includes a spring b and a recess therefor and a supplementary portion 39d and a finger a therefore wherein teeth c are provided on supplementary portion 39d which teeth are biased by spring b against the pinion 35 to thereby lock against pinion 35 and prevent
30 the motion of the carrier when the window is removed. A sloped wall d is provided with the carrier supplementary portion 39d which is engaged by a separate simple latching and unlatching mechanism which thereby releases the supplementary portion away from the pinion or toward the pinion when the latch is
35 opened. Therefore when the latch engages the supplementary portion d it will drive the supplementary portion 39d away from the pinion 35 thereby allowing free motion of the pinion in normal

- 32 -

circumstances. However when the latch is disengaged the portion 39d will be free to move as biased by the spring b toward locking the pinion 35 via the teeth c of the supplementary portion 39d. The alternate shoe of Figure 6 and 7 has an opening 39a within which
5 the extension 35a passes to engage the connecting member 30 as previously described. The rollers 39b engage with the notches as shown to improve the motion of the carrier in the track.

Referring now to Figure 8, 9 and 10 there is illustrated an alternative embodiment of the invention to maintain the carrier
10 pivots 61, 65, 60 and 81 in substantially parallel alignment and thereby eliminate the need for braking mechanisms. Figure 8 is illustrated as a tilt and slide frame in ghost line with the window 70 also shown in ghost line having pivot 75 and 71. The pivots 75 and 71 engage with openings within the shoe 61 and 65 in the manner
15 which is known. These pivot pins 75 and 71 may be removed from these shoes merely by retracting them from their locked positions. The sash 70 therefore is moved on the carrier 81, 82 and 83 proximate the bottom thereof in the track portions as shown and within carrier 60 on the top thereof. A similar sash arrangement
20 would be arranged for the other shoes as well but for simplicity sake this is not illustrated. The important aspect is that a cable 91 is connected to the carrier 60 and the carrier assembly 81, 82 and 83 substantially as shown in Figure 9, so that when the window moves toward the right hand side of the drawing that both carriers
25 will move an equal amount by the movement of the cable maintaining the pivots 75 and 71 within the shoes 60 and 81 substantially parallel at all times. Similarly, a cable 90 is provided which moves in conjunction with the carrier 63, 62 and 61 and the shoe 65, as best seen in Figure 9, so that as the shoe 65 is moved in
30 a direction D2 that the carrier 61, 62 and 63 will also be moved in the direction D2. Figure 9 therefore shows the path of the cable connecting the carrier described above.

In order to allow for the movement of the cable the unique pulley arrangement is illustrated in Figure 10 wherein the
35 cable will travel through the respective channels 107, 108 and 105a within the wheel 105, or through 106, 104, 105a within the opposite wheel or pulley 105. Assembly 101 is therefore provided

- 33 -

which is affixed within the window frame via opening 101a and a fastener, not shown, which assembly allows for the movement of the cable and hence the carriers in a manner as best seen in Figure 9.

5 Referring now to figures 11 and 12 there is provided a locking mechanism for the shaft 30 which may be used with any lousier assembly. A handle assembly H is provided including a stationary portion H2 fixed to the sash 21 and a moveable spring biased portion H1 biased to a continual locked position via spring
10 leaf S2. The handle portion H1 includes a pivot H4 and detent portions H5 and H6. Normally the spring S2 will cause the handle portion H1 to remain in engagement at detents H5 and H6 with gear portion or serrations 30Z of the shaft 30. Therefore the window or door is locked in that position and cannot be pivoted or slid. When a
15 user engages the handle H1 and presses it towards H2 the detents H5 and H6 release from the gears 30Z and hence the window or door may be repositioned as desired. At that repositioned location when the user releases the handles the window or door will again become locked.

20 Referring now to Figures 13, 13a, 13b, 13c and Figure 18, there is illustrated a track portion 18 and 19 which is to be installed within, as shown in Figure 18, the sill and header 220 of a frame assembly also including upwardly extending jamb portions 220a. The track portions 18 and 19 therefore are installed within
25 the profiles as seen in Figures 2b and 18 by the provision of a locking block assembly 200 which includes an adjuster nut 210 which engages the rack portion 18x of the rack 18a of the track profile 18 as best seen in Figure 13a. The profile therefore includes the rack 18a, a riding portion for the rollers 18e which will be
30 explained hereinafter, and a recess 18d wherein a carrier as best seen in relation to Figure 14 rides with the exception of the rollers. The track 18 therefore must be locked in position in the sash 220, and this is affected by the locking block 200 and the moveable nut 210. As best seen in Figure 13c, the track is inserted into the sill
35 profile as shown so that the carrier may ride on the track. The assembly of Figure 17 for the sash is therefore engaged with the carrier. The block 200 therefore is screwed down through the

- 34 -

profile 15 into the wooden frame member not shown via opening 15c in the profile and 204 in the block 200. Two fasteners 205 therefore are provided, and as shown in Figure 13, they are inclined at an angle to the vertical in order to allow for the provision of an
5 adjuster 206 which is accessible through the opening 207 in the block 200 wherein a cap screw having a head 206a having an allen key type access slot is provided. The threading 207b extends down to the end 207a proximate the nut 210.

As best seen in Figure 13, the lock block 200 and the
10 locking nut 210 have a profile substantially as shown with a triangular shaped cut out provided adjacent the top thereof and wherein abutting portions 201 and 203 are provided to engage with the flanges 15b and 15a of the profile 15 of the sill portion 220. The triangular cut-out portion includes an upwardly vertical face
15 202a, and bottom 202. Similarly the nut has a shoulder 211 provided and a substantially triangular shaped cut out 212 and an upwardly extending face 212a for engaging with the sill profile 15 similar to that which is illustrated and described in relation to Figure 13. The rotation therefore of the cap screw 206 results in
20 the movement of the nut 210 in relation to the block 200 which is fastened in position. The adjustment therefore of the screw allows for the thread to engage a threaded opening not shown in the nut 210 so that the rack portions 213a provide engagement with the rack 18a of the track portion 18 and will allow for fine adjustment
25 in the positioning of the track 18 and the locking in position of the track. It has been found sufficient that by providing the block and the adjustment of the nut, it will sufficiently position and lock the track in position and allow for the adjustment of the track which will then further allow for the adjustment of the pivots as best seen
30 in Figures 1, 1a, 1b, 1c, Figure 2, Figure 3 and Figure 17 so that the parallelism is not lost, and if fine adjustments once installed are required to the window sash to maintain the parallelism of the system, this is very easy to do. Should the system go out of parallel and require fine adjustment to restore the parallelism, a mere
35 rotation of the head 207 is required for both the sill and headers 220 so that the system is squared.

- 35 -

The notch portion defined by the faces 202a and 202 have a unique purpose in that the latch portion 251 as well as 250, as best seen in figure 17, will engage with the face 202a and provide a lock detent for the lock 251. This adds reinforcement to the lock provided in that should the triangular shaped detent of the block not be provided, then the lock 251 would engage flange 15a and in time would wear out that flange in that particular locking position. The nut 210 has a similar function so that either the nut or the block can function as the detent for the latch. Specifically in Figure 18, the screw 206 is shown being engageable from the nut toward the block, and in fact it is accessible in either direction as shown in Figure 13 and Figure 18 without changing the advantages of the system. For access purposes, depending on the installation and the type of window, it may be easier to adjust as shown in Figure 18 as opposed to Figure 13. Preferably the block is made from fiber-filled nylon. Alternatively, the block may be made from aluminum. The nut may be made from fiber-filled nylon as well.

Referring to Figures 14, 14a and 18, there is illustrated a carrier 39x which includes a pivot portion 35 for engaging with the shaft portion 32 and 34c of the pivot assembly and for carrying that shaft assembly and the pivoting end of the sash in the track 18 and 19 respectively of Figure 18. The carrier includes a portion 39y provided therewith to carry the rollers 39b therein. This is very similar to the carrier illustrated and described in the previous descriptions and more specifically in relation to Figure 1a and 1b, with the exception that the details of the carrier were not shown at that time in relation to the thrust wheel 35c provided on the bottom.

The carrier, as best seen in Figure 1a therefore rides on the rollers on the track profile seen in Figure 13A on the surfaces 18e for the roller wheels 39b and in the notch or cut-out recess 18d for the side portions adjacent the roller 39b at 39z. The pinion portion 35 therefore has an opening 35b for receiving the shaft 32 which extends toward the bottom of the opening 35d and which opening 35b as best seen in Figure 14 is compatible with the shape of the shaft 32. The outer surface 35a of the opening 35b is compatibly shaped with the opening in the carrier so that the

- 36 -

opening 35b may be accessible to the shaft 32. At the bottom of the pinion portion 35 is a thrust wheel carrying portion 35e which carries the thrust wheel 35c. The thrust wheel 35c therefore rides in between the shoulders 18c and 18b on the surface 18d of the track profile 18. The thrust wheel is provided to accommodate any wind load which may be placed on the system when the window is opened. Further, in the normal meshing of gears with a rack, there is a thrusting force created as the pinion 35 moves on the rack 18x. Therefore, the thrusting wheel will engage from time to time the shoulders or the surfaces defined by the shoulders 18c and 18b so as to maintain the parallelism and the accuracy of the installation of the window system. A pinion gear 35a is therefore provided between the thrust wheel 35c and the pivot receiving opening 35b which operates substantially as described in relation to Figure 1A and Figure 1 in that as the window rotates the pivot rotates causing the gear 35a to rotate and move on the track. This is particularly advantageous when the pivot assembly is provided on a casement window as best seen in relation to Figure 1A in that it is desirable to have the window move away from a pocket provided in the window jamb as best seen in relation to Figure 1D so that the sash profile will not engage the jamb profile but will readily clear the jamb profile as the window is opened. For example, as best seen in Figure 1D, proximate the top thereof, it may be readily seen that a pocket is provided in the jamb profile so that the pivot assembly 30 is accommodated at that end of the window. However, a flange portion unlabelled engages the sash cover portion so that within the jamb J1 there is a pocket J2 provided which improves the seal of the window in that the cover portion SC extends into the pocket J2 when the sash is closed. However, when the sash is pivoted as in the case with the casement window of Figure 1C, the pinion gear when pivoted will move the sash and the sash cover SC out of the pocket J2 away from the jamb J1 and provide suitable clearance so that the sash cover SC will not engage with the jamb portion J3 which is a flange and therefore will clear easily the pocket and all its enabling portions. When the casement window is closed, the opposite happens and the sash cover SC will engage the pocket J2

- 37 -

and be moved in position with the pivoting of the window to the closed position.

5 The rollers 39b therefore provide a smooth motion of the closure system in relation to the track which would not be present if the rollers were not provided since the track is made from aluminum. The rollers are not absolutely essential in every embodiment, however, it is preferred.

Referring now to Figure 15, there is illustrated two sashes side by side shown in end view. The sashes are made substantially as constructed in relation to Figure 17 wherein the sash 220 is defined by a central I-shaped portion 227 having an opening therein and two side abutting portions 225 and 226. A pocket therefore for receiving the glass G is defined at 222. Fin seal portions 221 are therefore provided for abutting the glass G which contains the normal known seal portion SX. The window sash profiles also include flange portions 224 proximate the opening opposite the glass G. Within that opening there is provided in use a closed cell caulking foam which is compressible at portion 240. This portion extends totally along the sash profile within the opening as shown with the exception of the portion adjacent the pivoting assembly. A cover portion therefore is provided at 230 which engages the tab portions 224 proximate each side of the sash profile. This cover portion when inserted is flexed downwardly as the closed cell foam 240 is compressed as best seen in Figure 15a so that the flange portions of the cover at 230a engage with the flange portion of the sash at 224 to provide a compressed seal for the track cover 230. The track cover is defined as a track cover although it does occupy the sash as a component thereof in that as the sash is closed over the opening defined between the flange portion 16a and 16b as best seen in Figure 15a, the snap cover portion will extend down into and engage with the flanges 16a and 16b, thus covering the track and snapping into position each time the sash is opened and closed. The typical seals BX and BY are provided as is known in the art.

35 Alternatively, as best seen in Figure 1D, the sash covers may include alternative embodiments shown proximate the jamb portions 16a and 17a of the window assembly. Alternatively, a

- 38 -

cover portion may be provided over the track portion 15 of sill portion 220 and header portion 220 of Figure 18 that engages with the sash profile in a similar way to that of the track cover of Figure 15a with the exception that the track cover only extends over the second half of the track, that is to say the second half not carrying the window. For example as shown in Figure 2, the wheel portion 39a may be eliminated and the track cover may extend along the track portion opposite the pivot assembly so that the sash may slide on the track cover and be assisted to be supported by that track cover only in the second half of the track profile thereby eliminating the second carrier of Figure 2. The track cover therefore in Figure 2 as an example would extend from the carrier 39a toward the left side of the page to allow the pivot assembly 35 to move to approximately the position of the present carrier 39a wherein it would engage the track cover. In the movement of the carrier 35 to that position, the other end of the window would already be supported by the track cover. This installation therefore would eliminate the carrier 39a.

Referring now to Figure 16B, there is provided locking detents 250 and 251 which engage with the locking detent portions 202 and 212 of the lock and nut portions 200 and 210. These locking portions 250 therefore and 251 are operated by a handle 260 as best seen in Figure 16A which is rotatable to cause the motion of the rack portion 265 and the detent 250 into and out of the locking abutment provided with the lock block and the lock nut 200 and 210 respectively. In Figures 16, 16A and 16B, the installation is provided for a casement window assembly. In the United States Patent Application described in the Summary of the Invention which was incorporated by reference, there is no provision of a casement-style window lock. Nor was there the provision of a lock block or nut detents 210 and 200 respectively. The handle therefore 260 is rotated by the user which causes the movement of the corresponding pinion gear 261, the rotation of the pinion gear 261 affects the movement of the rack 265, and the latch engaging portion 250a and 251a carried within the housings 255 and 254 respectively as best seen in relation to Figure 17. The rotation of the pinion will therefore also cause the motion of the

- 39 -

rack portion 266 sufficiently as provided by the opening 266a of said rack portion to allow for engagement of said rack portion with said rack portion 265 with the bottom portion affecting the latching and unlatching of detent 251. Intermediate the two latching portions for the casement window is provided a second pinion 267 which is rotated effectively by the movement of the rack portion 266. Rotation of the pinion 267 causes rotation of the pinion sector 268 which is engaged with the locking detent 269 for the latch plate 270 and the detent 271 thereof. This latch plate is typical for casement windows as is the movement of the lock 269, i.e. the rotation thereof. However, with the central locking system provided with this invention, it is the one handle operation of both the detents 250 and 251 and the casement window lock 269 which is in combination the essence of the central locking system. Alternatively, the casement window portion may be left out and the essence of the locking system therefore includes the locking block in the track which provides a detent for the locks 250 and 251 respectively.

As best seen in relation to Figure 17, there is provided a cover C(x) which hooks into the sash profile similarly to the cover 230 previously described in relation to Figures 15 and 15A through which the handle portion 260 extends. Therefore, the latch assembly is contained within the sash profile, and the only portion extending outside of the sash profile is the handle portion. This handle portion is considerably smaller than the normal handle portion provided with a casement window which is typically rotary, and there is a tremendous elimination of components for a casement-type window. In fact, this will be described hereinafter.

Referring to Figure 17, there is shown an exploded perspective view of the window assembly which will fit into the track profile similar to Figure 18, but more specifically which may be designed for a casement window. The sashes 220 are provided with an opening 227 wherein a corner connector 280 is provided which extends into the opening 227 proximate all four corners and eliminates the necessity for welding. Clip portions 281 bite into the vinyl and are tapered in a direction so as to prevent the removal of the corner connectors once inserted within opening 227. This snap

- 40 -

lock feature therefore provides for the installation of the corner connectors and the quick fastening of the sash profile around the glass G. The track covers 230 are therefore provided and snapped into position once the closed cell foam, best seen in Figure 15a at 240, is inserted within the opening of the sash profile. The hardware including the carriers, best seen in Figure 18, which are then assembled within the opening opposite the glass of the sash proximate each jamb portion in use. The hardware therefore including the top and bottom track engaging portion 39x and 37x, the shaft 32, the connector 31bx, the other shaft 31, and the small shaft 34c are provided proximate the pivoting end of the window assembly within the sash profile enclosed by a cover similar to that of cover CX. The central lock as described in relation to Figures 16, 16A and 16B is therefore inserted within the other opening of the sash profile and assembled and covered by the cover CX. The window sash is now available for installation within the frame assembly of Figure 18 once the carrier portions 39x are engaged with the respective shafts 32 and 34c. The block portions 200 are therefore locked in position once the track is installed in the frame, and the nut portions are adjusted to allow for the parallelism of the carriers 39x within the tracks to ensure the parallelism of the sash so that it rides well within the track portions. The window is therefore assembled.

For a casement window, all of the prior art levers and latch mechanisms are substantially eliminated. This means a great deal to window manufacture in that there are a considerable number of screws and fasteners to hold down the prior art lever linkages of the prior art systems. In the present invention, only the latch block fasteners are provided. The rest of the window assembly merely snaps together with a friction fit of the sash profiles, the sash profile covers and the frames. A minimum of assembly labour is therefore required with the installation of this window assembly. In one particular situation where an old style double-hung window is installed within an opening, it may be conveniently removed by an installer and the present invention may be installed in any of its embodiments including a casement window.

This is heretofore unknown in that a casement window occupies a certain standard space in the industry, and because of the linkage systems and the known systems, it is not possible to provide a larger window. With the present invention, a larger casement window may be provided which is easily installed with the minimum amount of labour and assembly time required. Should the window now be mis-aligned for any reason, it may be easily adjusted by the rotation of the screw 206 provided. A sophisticated user therefore could easily adjust this once instructed over the phone by an installer, or alternatively the installer may return for a quick adjustment at any time. Also, the window assembly is less likely to go out of adjustment because of the great care taken in the development of the precision of the assembly.

A method therefore of assembling the window may be considered as described in the above-mentioned description wherein, firstly the sash components are assembled by the quick fastening feature of the corner locking portions which are inserted within the opening of the sash profiles provided and provide one-way friction fit. The closed cell caulking is therefore inserted within the top and bottom of the sash assembled and these portions are covered by the track covers by the compression of the closed cell foam and the engagement of the tabs of the track cover with the tabs of the sash profile. The hardware is then installed along the vertical portions of the sash within the openings thereof opposite the glass which is then covered by a sash cover portion provided. The hardware located proximate the pivoting end is therefore installed on the carrier portions and inserted within the track portion within the sill and header, for example of a window assembly. The window is therefore closed in position with the sash covers or track covers located proximate the sill and header snapping into the frame and closing any path for air to enter the window and pass the primary seals provided as best seen in relation to the Figure 15A. The track covers also provide blockage of light, air and the friction fit of the sash into the track portions. By providing a track cover along the track remote the pivoting end of the window, this track cover may be used as support as well for the window assembly.

- 42 -

In another embodiment not shown, a double casement window is provided which is provided in a straight-line window, that is to say a frame is provided wherein a central mullion is disposed. A central mullion separates two casement windows, one
5 opening as a mirror image of the other and containing all of the elements described above in relation to the pivot assembly and the central locking system and track system.

As many changes can be made to the preferred embodiments of the invention without departing from the scope or
10 intent thereof; it is intended that all matter contained herein be considered as illustrative of the invention and not in a limiting sense.

- 43 -

THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE
PROPERTY OR PRIVILEGE IS CLAIMED ARE AS FOLLOWS:

1. A closure assembly comprising a track and a slidable
5 and pivotable closure member, the closure member being engaged
with the track proximate first and second pivots adjacent the
pivotable end of the member, the first and second pivots being
interconnected by a multiple segment shaft (for example at least
10 two portions) (for example telescoping) which provides for
accurate installation, retention, removal, adjustment and alignment
of the first and second pivots in a substantially parallel line for
pivotally supporting the closure member so that it may be safely
and securely pivoted away from the closure assembly, whereby the
15 first and second interconnected pivots are adapted to remain
engaged with the track while supporting the closure member both
when it is pivoted away from the closure assembly and when it is
slidable relative to the track.

2. The closure assembly of Claim 1 further comprising a
20 carrier traveling within said track having interconnected first and
second portions, the first portion being engaged with the pivots of
the closure member and the second portion being spaced within the
track from the first portion, the carrier to assist sliding movement
and pivoting movement of the closure member.

25 3. The closure assembly of Claim 2 wherein the
interconnected portions are adjustable in length.

4. The closure assembly of Claim 2 the first portion further
30 comprises an opening within which the first and second pivots are
disposed to cooperate with the carrier portion.

5. The closure assembly of Claim 4 wherein the first and
second pivot portions further comprise a rotatable pinion disposed
35 therewith for facilitating the movement of the carrier relative to
the track.

- 44 -

6. The closure assembly of Claim 5 wherein the rotatable pinion moves in cooperation with a rack disposed with said track.
7. The closure assembly of claim 1, 2, or 5 wherein the
5 closure member further comprises latching means for latching the closure member to prevent pivoting thereof when the closure member is slidable relative to the track.
8. The closure assembly of Claim 7 wherein the latching
10 means is a central locking member disposed with the closure member.
9. A pivoting and sliding closure assembly comprising:
i) an opening extending within a frame
15 ii) the frame having disposed therein or attached thereto track portions extending in a substantially parallel direction to the extensions of said frame portions;
iii) at least one closure member slidable within said track portions and pivotable at least one end thereof and latchable
20 in the track at the other end thereof;
iv) each track portions having disposed therein at least two pivot shoes adjacent the pivoting end of the closure member, each shoe being substantially compatibly shaped with the track and having a top and bottom, (preferably having rolling
25 means disposed therein for assisting the movement of the pivot shoe), each shoe adjacent the pivoting end of the closure member having disposed therein an opening extending from the top toward the bottom of the carrier wherein pivot means are disposed, said pivot means being interconnected by a multiple segment shaft (for
30 example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment of the first and second pivots in a substantially parallel line for pivotally supporting the closure member for safe and secure pivoting away from the closure assembly;
35 v) the closure member having latching means provided therewith for latching the at least one closure member in relation to the track to prevent the closure member from pivoting

- 45 -

upon its pivot means when the closure member remains slidable with said track

- vi) the at least one closure member being braced from sagging by the multiple segment shaft interconnecting the pivot means disposed with each track, the substantially parallel line of the pivots provided by the a multiple segment shaft preventing the pivot means from sagging and/or disengaging from the relevant track when the at least one closure member is rotated to an open position and/or when it remains slidable within said track.

10

10. The closure assembly of Claim 9 wherein the pivot shoes have rolling means disposed therein for assisting the movement of the pivot shoe.

11. The closure assembly of Claim 9 wherein the pivots further comprise a rotatable pinion for facilitating the movement of the carrier relative to the track .

12. The closure assembly of Claim 9 wherein the closure member further comprises latching means for latching the closure member to prevent pivoting thereof when the closure member is slidable relative to the track wherein the latching means is a central locking member disposed with the closure member.

13. The closure assembly of Claim 9 wherein the pinion moves in cooperation with a rack disposed with said track.

14. The closure assembly of Claim 1 or 9 wherein said closure assembly further comprise a window sash being a casement, double hung, or tilt and slide installation or, a door or a patio door.

15. The closure assembly of Claim 9 wherein Jambs headers and sills are provided with said frame and said closure member further comprises a window sash.

- 46 -

16. The closure assembly of Claim 9 wherein Jambs headers and sills are provided with said frame and said closure member further comprises a door.

5 17. The closure assembly of Claim 9 wherein Jambs headers and sills are provided with said frame and said closure member further comprises a patio door.

18. A pivoting and sliding closure assembly comprising:

10 i) an opening extending within a peripheral frame said peripheral frame including a header portion, a sill portion and two vertically extending jamb portions;

ii) the sill and header portions or the two jamb portions having disposed therein or attached thereto track portions
15 extending in a substantially parallel direction to the extensions of said peripheral frame portions;

iii) at least one closure member slidable within said track portions and pivotable at least one end thereof and latchable in the track at the other end thereof;

20 iv) each track portions having disposed therein at least two pivot shoes adjacent the pivoting end of the closure member, each shoe being substantially compatibly shaped with the track and having a top and bottom, (preferably having rolling means disposed therein for assisting the movement of the pivot
25 shoe), each shoe adjacent the pivoting end of the closure member having disposed therein an opening extending from the top toward the bottom of the carrier wherein pivot means are disposed, said pivot means being interconnected by a multiple segment shaft (for example at least two portions) (for example telescoping) which
30 provides for accurate installation, retention, removal, adjustment and alignment of the pivots in a substantially parallel line for pivotally supporting the closure member for safe and secure pivoting away from the closure assembly;

35 v) the closure member having latching means provided therewith for latching the at least one closure member in relation to the track to prevent the closure member from pivoting

- 47 -

upon its pivot means when the closure member remains slidable with said track;

vi) the at least one closure member being braced from sagging by the multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment interconnecting the pivot means disposed with each track, the substantially parallel line of the pivots provided by the multiple segment shaft preventing the closure member from sagging and/or disengaging from the relevant track when rotated to an open position or when it remains slidable within said track.

19. The closure assembly of Claim 18 wherein said closure member is a window sash being a casement installation.

20. The closure assembly of Claim 18 wherein the closure member further comprises latching means for latching the closure member to prevent pivoting thereof when the closure member is slidable relative to the track wherein the latching means is a central locking member disposed with the closure member.

21. The closure assembly of Claim 18 wherein the closure member is a window sash being a double hung, or tilt and slide installation.

22. The closure assembly of Claim 18 wherein said closure member is a door.

23. The closure assembly of Claim 18 wherein said closure member is a patio door.

24. The closure assembly of Claim 18 wherein the pivots further comprise a rotatable pinion for facilitating the movement of the carrier relative to the track.

25. The closure assembly of Claim 24 wherein said pinions move in cooperation with a rack disposed with said track.

26. For use in a pivoting and sliding closure assembly, a closure member slidable within a guiding channel and pivotable therefrom, the closure member having a substantially rectangular frame having a top and bottom, and having engaged at its top and bottom at one end pivots for engaging a first and second shoe, and having disposed at the other end thereof proximate its top and bottom user accessible means for engaging the guiding channel (preferably wherein said user accessible means is a central lock);
- 10 said shoes being slidable in said guiding channel and comprising a substantially rectangular body having a top and bottom (preferably made from thermoplastic material) and preferably having disposed proximate the bottom thereof at least one roller or wheel), said shoes having disposed therewith pivot
- 15 means (preferably the pivot means may further comprise a rotatable pinion for facilitating the movement of the carrier relative to the track preferably in cooperation with a rack disposed with said track) to engage with the shoes, said pivot means being interconnected by a multiple segment shaft (for example at least
- 20 two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment of the pivot means, each shoe having an opening for said pivot means, the opening extending from proximate the top towards the bottom of said shoe, whereby the closure member upon the pivot means
- 25 pivoting away from the guide channel is braced from sagging by the a multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment and interconnecting of the pivot means disposed with each channel, the substantially
- 30 parallel line of the pivots provided by the multiple segment shaft (for example at least two portions) (for example telescoping) preventing the closure member from sagging and/or disengaging from the relevant track when rotated to an open position or when it remains slidable within said track.
- 35
27. The closure assembly of Claim 26 wherein said user accessible means is a central lock.

- 49 -

28. The closure assembly of Claim 26 wherein said shoes are made from thermoplastic material.
- 5 29. The closure assembly of Claim 26 wherein said shoes have disposed proximate the bottom thereof at least one roller or wheel.
- 10 30. The closure assembly of Claim 26 wherein the pivot means further comprises a rotatable pinion for facilitating the movement of the carrier relative to the track.
- 15 31. The closure assembly of Claim 30 wherein said pinion moves in cooperation with a rack disposed with said track.
32. The closure assembly of Claim 26 wherein the interconnecting means engages with the edge of the framing sections for the closure member.
- 20 33. The closure assembly of Claim 26 wherein said closure member is a window sash.
34. The closure assembly of Claim 26 wherein said closure member is a door.
- 25 35. The closure assembly of Claim 26 wherein said closure member is a patio door.
- 30 36. A closure assembly comprising a track and a slidable and pivotable closure member, the closure member being engaged with the track proximate first and second pivots adjacent the pivotable end of the member, the first and second pivots being connected by connecting means to retain and align the first and second pivots in a substantially parallel line for pivotally supporting the closure member so that it may be safely and
- 35 securely pivoted away from the closure assembly, whereby the first and second connected pivots are adapted to remain engaged with

- 50 -

the track while supporting the closure member both when it is pivoted away from the closure assembly and when it is slidable relative to the track.

- 5 37. The closure assembly of Claim 36 wherein the connecting means is a cable system connecting the upper and lower pivot shoes to move in and be maintained in substantially parallel positions at all times.
- 10 38. Hardware for a closure assembly having a track and a slidable and pivotable closure member, the closure member being engaged with the track proximate first and second pivots adjacent the pivotable end of the member, the hardware comprising the first and second pivots being interconnected by a multiple segment shaft
15 (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment of the first and second pivots in a substantially parallel line for pivotally supporting the closure member so that it may be safely and securely pivoted away from the closure
20 assembly, whereby the first and second interconnected pivots are adapted in use to remain engaged with the track while supporting the closure member both when it is pivoted away from the closure assembly and when it is slidable relative to the track.
- 25 39. Hardware for a closure assembly having a track and a slidable and pivotable closure member, the closure member being engaged with the track proximate first and second pivots adjacent the pivotable end of the member, the hardware comprising the first and second pivots being connected by a cable system connecting
30 the upper and lower pivot shoes to move in and be maintained in substantially parallel positions at all times to retain and align the first and second pivots in a substantially parallel line for pivotally supporting the closure member so that it may be safely and securely pivoted away from the closure assembly, whereby the first
35 and second connected pivots are adapted to remain engaged with the track while supporting the closure member both when it is

- 51 -

pivoted away from the closure assembly and when it is slidable relative to the track.

40. The hardware of Claim 39 wherein the connecting means is a cable system connecting the upper and lower pivot shoes to move in and be maintained in substantially parallel positions at all times.

41. The assembly of claim 1, 9, 18, or 26 wherein a resiliently biased lock and handle is provided which normally locks the shaft from operation until the handle is operated by a user wherein the lock is disengaged from the shaft and allows the shaft to rotate and when the handle is released again locks the shaft allowing for continuous locking of the assembly at any position.

42. The hardware of claim 38 wherein a resiliently biased lock and handle is provided which normally locks the shaft from operation until the handle is operated by a user wherein the lock is disengaged from the shaft and allows the shaft to rotate and when the handle is released again locks the shaft allowing for continuous locking of the assembly at any position.

43. The assembly of claim 1, 9, 18, or 26 wherein when embodied in a tilt and slide or double hung window the inside rack portions provided within the track of the assembly, which extend the full width of the frame, curve towards the stationary closed position for the window assembly and provide a closed window assembly in which both sashes are oriented in a straight line.

44. The assembly of claim 1, 9, 18, or 26 embodied in a casement window wherein a link having two ends is fastened at one end proximate the center of the bottom of the window sash and proximate the other end adjacent the end of the sill of the window frame to allow for full operation of the casement window from a fully closed to a fully open position and the movement of the pivoting end of the window towards the opposite end so as to allow

- 52 -

full access to the outside of the window and the easy cleaning thereof.

45. The assembly of claim 44 wherein the link is removable
5 to allow total reversing of the window for cleaning and/or removal purposes.

46. The assembly of claim 1, 9, 18, or 26 embodied in a tilt
and slide, casement or double hung window wherein a
10 retractable screen is provided disposed within the header of the
assembly which accumulates on and pays out from a spring biased
roll disposed within said header, the screen being retractable for
egress or cleaning purposes, and available as desired by providing a
detent on the sill engageable with the screen when in its operatable
15 position.

47. The assembly of claim 1, 9, 18, or 26 wherein the rack
disposed with the track is made from aluminum and formed in
three separate steps so as to minimize the amount of vertical
20 creeping of the rack when formed.

48. The assembly of claim 47 wherein the rack also acts as a
liner to distribute the load of the sash and minimize distortion of
the vinyl track.
25

49. A closure assembly comprising a track and a slidable
and pivotable closure member, the closure member being engaged
with the track proximate first and second pivots adjacent the
pivotable end of the member, the first and second pivots being
30 interconnected by a multiple segment shaft (for example at least
two portions) (for example telescoping) which provides for accurate
installation, retention, removal, adjustment and alignment of the
first and second pivots in a substantially parallel line for pivotally
supporting the closure member so that it may be safely and
35 securely pivoted away from the closure assembly, whereby the first
and second interconnected pivots are adapted to remain engaged
with the track while supporting the closure member both when it is

- 53 -

pivoted away from the closure assembly and when it is slidable relative to the track.

50. A pivoting and sliding closure assembly comprising:
- 5 i) an opening extending within a frame
- ii) the frame having disposed therein or attached thereto a first and second track portion extending in a substantially parallel direction to the extensions of said frame portions;
- 10 iii) at least one closure member slidable within said track portions and pivotable at least one end thereof and latchable in the tracks at the other end thereof;
- iv) each track portions having disposed therein a pivot shoe adjacent the pivoting end of the closure member, said shoe being substantially compatibly shaped with the track and
- 15 having a top and bottom, (preferably having rolling means disposed therein for assisting the movement of the pivot shoe in the track), the shoe having disposed therein an opening extending from the top toward the bottom of the shoe wherein pivot means are disposed, said pivot means of said shoe disposed with said first track portion
- 20 being interconnected with the pivot means of the shoe in the second track portion by a multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment of the first and second pivots in a substantially parallel line for pivotally
- 25 supporting the closure member for safe and secure pivoting away from the closure assembly;
- v) the closure member having latching means provided therewith for latching the at least one closure member in relation to the track to prevent the closure member from pivoting
- 30 upon its pivot means when the closure member remains slidable with said track,
- vi) the at least one closure member being braced from sagging by the multiple segment shaft interconnecting the pivots disposed with the pivot shoe of each track, the substantially parallel
- 35 line of the pivots provided by the a multiple segment shaft preventing the pivots from sagging and/or disengaging from the

- 54 -

relevant track when the at least one closure member is rotated to an open position and/or when it remains slidable within said track.

51. A pivoting and sliding closure assembly comprising:

- 5 i) an opening extending within a peripheral frame said peripheral frame including a header portion, a sill portion and two vertically extending jamb portions;
- 10 ii) the sill and header portions or the two jamb portions having disposed therein or attached thereto first and second track portions extending in a substantially parallel direction to the extensions of said peripheral frame portions;
- 15 iii) at least one closure member slidable within said track portions and pivotable at least one end thereof and latchable in the track at the other end thereof;
- 20 iv) each track portions having disposed therein a pivot shoes adjacent the pivoting end of the closure member, said shoe being substantially compatibly shaped with the track and having a top and bottom, (preferably having rolling means disposed therein for assisting the movement of the pivot shoe), said shoe
- 25 having disposed therein an opening extending from the top toward the bottom of the carrier wherein pivot means are disposed, said pivot means for said shoes disposed within said first and second tracks being interconnected by a multiple segment shaft (for example at least two portions) (for example telescoping) which
- 30 provides for accurate installation, retention, removal, adjustment and alignment of the pivots in a substantially parallel line for pivotally supporting the closure member for safe and secure pivoting away from the closure assembly;
- 35 v) the closure member having latching means provided therewith for latching the at least one closure member in relation to the track to prevent the closure member from pivoting upon its pivot means when the closure member remains slidable with said track;
- vi) the at least one closure member being braced from sagging by the multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment

- 55 -

interconnecting the pivot means disposed with each track, the substantially parallel line of the pivots provided by the multiple segment shaft preventing the closure member from sagging and/or disengaging from the relevant track when rotated to an open position or when it remains slidable within said track.

52. The assembly of claim 49, 50, or 51 wherein the first and second pivot portions further comprise a rotatable pinion disposed therewith for facilitating the movement of the carrier relative to the track.

53. The assembly of claim 52 wherein the rotatable pinion moves in cooperation with a rack disposed with said track.

54. Hardware for a closure assembly having a track and a slidable and pivotable closure member, the closure member being engaged with the track proximate first and second pivots adjacent the pivotable end of the member, the hardware comprising the first and second pivots being interconnected by a multiple segment shaft (for example at least two portions) (for example telescoping) which provides for accurate installation, retention, removal, adjustment and alignment of the first and second pivots in a substantially parallel line for pivotally supporting the closure member so that it may be safely and securely pivoted away from the closure assembly, whereby the first and second interconnected pivots are adapted in use to remain engaged with the track while supporting the closure member both when it is pivoted away from the closure assembly and when it is slidable relative to the track.

55. The hardware of claim 54 wherein said hardware is embodied in a casement window wherein a link having two ends is fastened at one end proximate the center of the bottom of the window sash and proximate the other end adjacent the end of the sill of the window frame to allow for full operation of the casement window from a fully closed to a fully open position and the movement of the pivoting end of the window towards the opposite

- 56 -

end so as to allow full access to the outside of the window and the easy cleaning thereof.

56. The hardware of claim 55 wherein the link is removable
5 to allow total reversing of the window for cleaning and/or removal purposes.

57. The assembly of claim 49, 50, 51, or 54 wherein a
10 retractable screen is provided disposed within the jamb of the assembly which accumulates on and pays out from a spring biased roll disposed within said jamb, the screen being retractable for egress or cleaning purposes, and available as desired by providing a detent on the sill engageable with the screen when in its operatable position.

15 58. The assembly of claim 53 wherein the frame portions, for example the headers, vertical jambs or sills are formed separately from the track, the track further comprising an integral rack portion proximate one side thereof, said rack portion including
20 a plurality of teeth extending substantially from end to end of said track, and for engagement with the rotatable pinion of said carrier which facilitates the movement of the carrier relative to the track, the track being fixed in position relative to the headers, sills and/or jambs by the provision of two supplementary portions, the first
25 supplementary portion being a block which has two ends, a top and a bottom, the block having disposed in use proximate the top thereof opening to receive fasteners which openings extend to the bottom of the block, the fasteners for engagement with the frame portion and preferably the wooden base portions of the frame and
30 are provided to lock the first block in position in relation to the end of the track remote the pivoting end of the closure member, and thereby fixing the track in position, the first block having disposed therewith an adjuster moveable in relation to said block in a direction extending towards said track and preferably rotatable,
35 said adjuster being engageable with a second supplementary portion, and preferably a nut portion having track shaped abutting portions proximate one side thereof, and for engagement with said

- 57 -

track, the second portion having elements provided therewith which are engageable with said adjuster and said track, said adjuster being moveable in position to move the track abutting portions in relation to the rack provided with the track, wherein
5 movement of said adjuster will move said second portion and preferably said nut in relation to said track and said rack in a direction toward and away from the block thereby adjusting the position of said track in relation to said frame portions and thereat fixing said rack in position wherein such an adjustment for the
10 track establishes and allows for the alignment or adjustment of the closure member and maintains the parallelism of the carrier in relation to for example both a bottom and a top track in the case of a tilt and slide or casement window, or the left and right side in the case of a double hung widow, so that the pivots remain
15 substantially parallel and square to one another.

59. The assembly of claim 58 wherein aluminum is used for the track, the track being formed from three separate steps so as to minimize the amount of vertical creeping of the rack when formed.
20

60. The assembly of claim 58 wherein the adjuster is a rotatable cap screw preferably having an opening therein for an allen key, and which is contained within an opening proximate one end of the first block remote the track and wherein said cap screw
25 is threaded into the second block or preferred nut, wherein rotation of the screw in relation to the fixed block, for example by an allen key, will cause the second block or preferred nut to move fore and aft in relation to the track and provide for a final adjustment or readjustment of the track in relation to the carrier in both the top
30 and bottom or side tracks of the window system depending on what window system is used.

61 The assembly of claim 58 wherein the block is manufactured from aluminum, and the adjuster nut is
35 manufactured from Delrin(TM).

- 58 -

62. The assembly of claim 58 wherein the block and nut are manufactured from fiber filled nylon.

63. The assembly of claim 58 wherein both the first block
5 and second nut further comprise a detent, for example a right angled triangle notch proximate the top thereof for engagement with a lock in use for a pivoting window, the lock being compatible with the detent.

10 64. The assembly of claim 58 wherein a pivot shoe is provided for engagement with said rack and track further comprising a carrier having a top and a bottom, the carrier having disposed proximate the bottom thereof means, and preferably slots, for retaining rollers, and the rollers in use thereof for providing the
15 smooth movement of the carrier within the track, preferably the rollers being engaged with a predetermined channel formed in said track, said carrier also having an opening disposed proximate the top thereof wherein a pivot gear is disposed, said pivot gear having a top and a bottom and having disposed proximate the top thereof a
20 pivot engaging portion for engaging the pivot of a closure member such as a window sash, said pivot gear having disposed proximate the bottom thereof an anti-thrusting wheel portion for engagement with a shoulder provided proximate each side of the track channel, for example to engage the shoulder of the channel as a result of
25 thrust which may be caused by the wind load on the closure member and the normal thrust caused by meshing of gears, the anti-thrusting wheel preferably being of a predetermined diameter of a dimension less than the channel of the track so as to minimize drag in the track, said pivot gear having disposed intermediate said
30 pivot engaging portion and said anti-thrust wheel portion a pinion gear portion for engaging the rack, wherein the closure member and specifically the pivots thereof engages with the carrier portion, wherein movement of said carrier portion will affect rotation of said pinion in relation to said track and the smooth movement of
35 the carrier along the track maintaining the parallelism, of said upper and lower pinions for the case of both a tilt and slide and

- 59 -

casement window, and said left and right pinions in the case of double hung windows.

65. The assembly of claim 64 wherein said carrier portion is made from Delrin(TM), and said pivot gear portion is made from nylon.

66. The assembly of claim 49, 50, or 51 wherein a profile forming the closure member (for example a sash profile) is provided and further comprises a cover disposed on the side of the profile opposite a glass, which cover extends substantially along the length of the profile and which has disposed proximate the sides thereof two flanges for locking engagement underneath flanges provided with the profile, said profile further including a space defined within said profile enclosed by said cover, said space containing in use a closed cell foam or the like, for example a closed cell caulking foam, which is compressible, said cover having disposed proximate the bottom thereof intermediate said flanges spring-loaded members, for example fingers, engageable with said foam, and preferably when installed slightly loading said foam to create a spring biased resistance of the foam against the cover further locking the cover in position with the profile, the cover is made from flexible material and when installed extends down from said profile toward the space defined within said track portion between the flanges thereof, the cover providing a locking flexible seal throughout the length of the closure member with the exception of the area adjacent the carrier portion located proximate the pivoting end of said closure member; wherein the use of a closed cell foam such as caulking foam or the like in the space within the profile provides resilience and strength to the cover along the length of the profile and therefore allows for the foam and cover together to provide a surface upon which the closure member may travel while the carrier moves in the track, the cover behaving as a seal for the profile and in use indirectly for the track to keep dust and other undesirable elements out of the track and out of the profile, and assists to prevent passing cold air.

- 60 -

67. The assembly of claim 66 wherein the cover is embodied with a casement window, a tilt and slide window or a double-hung window.

5 68. The assembly of claim 49, 50, 51, or 63 wherein there is provided a release mechanism for locking a closure member from pivoting movement in a closure assembly, said release mechanism further comprising operating means disposed with the closure member, and preferably with the window sash elements, said
10 operating means being provided intermediate the lockable ends of the closure member, and accessible to the user, when the closure member is provided within a tilt and slide window, the operating means being generally be disposed in a vertical plane provided with a vertical sash element so that the operating member when
15 operated will cause the locking and unlocking of the tilt and slide window and allow free movement thereof, when the operating means is provided in a double-hung window, the operating means being a handle disposed in a horizontal plane and being operable by the user to and from a locked and released position to allow
20 movement of the double-hung window, for example, pivoting thereof to access the exterior pane surface and provide cleaning thereof, when the closure member is a casement window sash, the operating member being be disposed in a substantially vertical direction and being operable by the user to and from a locked and
25 unlocked position, the operating means being user operable to and from a first locked position and a second unlocked position, the bi-directional locking means provided with the sash profile being moveable by the operation of said operating means to cause locking portions engaged with said bi-directional locking means to move in
30 and out of engagement with track portions (and in one embodiment the previously described block and nut portions) disposed proximate at least two opposed locations of said closure assembly, and when the window is a casement window further locking action resulting from the engagement of a third portion in and out of
35 locking engagement with a locking detent provided adjacent the jamb wherein the window sash is contained, the operation of the operating means in a first direction causing the locking portion to

- 61 -

move out of engagement with, the track portions or the detent provided with the track portion, and when a casement window is in use, the locking detent adjacent to the jamb, to therefore allow pivoting movement of the closure member, the movement of the
5 operating means in the second direction causing the locking portions to move into engagement with the track portions or the detent provided with the track portion and therefore prevent the pivoting movement of the closure member.

10 69. The assembly of claim 68 wherein the release mechanism for locking a closure member includes a handle portion which has provided proximate one end thereof a handle and proximate the other end thereof a pinion, said pinion being engageable with a rack portion proximate one side thereof and a
15 second rack portion proximate the other side thereof, said rack portions being engaged with locking portions which extend to the track or detent provided with the track in use to latch and unlatch the closure assembly, for example the window.

20 70. The assembly of claim 69 wherein a casement window is provided with the release mechanism, the pinion portion also engaging one of the rack portions which further engages a second pinion rotatable by the motion of the second rack, the second pinion being engageable with a latch portion including a pinion sector
25 provided therewith, causing the rotation of the latch portion into and out of engagement with a detent portion provided proximate the jamb of a casement window assembly, said single handle therefore operating both the locks proximate the track portion and when a casement window is used the lock proximate the jamb
30 portion.

71. The assembly of claim 49, 50, or 51 wherein there is provided a casement window assembly further comprising a jamb portion located proximate the pivoting end of a casement window,
35 preferably said window including a clip in flexible cover for the sash, said jamb portion including a pocket portion extending substantially towards the casement window sash and providing a

- 62 -

pocket for the pivoting end of the casement window wherein said carrier is disposed in use, thereby providing a recess or pocket within which the closed casement window proximate the pivoting end thereof is located and when a cover is provided with the sash to snap fit into, to improve the seal and weatherproofing of the casement window, said pinion upon pivoting of the casement window causing the rotation of said gears and the sliding motion of the pivoting end of the window away from the jamb pocket thereof to prevent binding of the pivoting end with the pocket extending with the jamb portion, thereby providing the sealing improvements to the casement window, wherein when the casement window is moved to the closed position, the pivoting end will move back into the pocket provided.

72. The assembly of claim 49, 50, 51 or 58 further comprising a conversion kit of components for a frame opening to convert a, a double-hung window or a tilt and slide window to a casement window assembly, said conversion kit comprising framing portions for containing track portions engageable with the framing portions of the window frame section (for example header and sill, or two vertical jamb members), said track portion, preferably being made from aluminum, and including a rack portion proximate at least one side thereof, a casement window sash having a carrier and interconnecting pivot assembly provided therewith and for insertion and operation with respect to the track portions of the frame, wherein said casement window fully fills the space occupied by the previously installed double-hung or tilt and slide window, and the jamb, sill, and header portions are installed in the space provided, wherein the existing window assembly is stripped out down to the wooden frame section, the installer installing the vinyl header sill and jamb section to the wooden frame members, the tracks then being installed, and preferably using the block and nut portions previously described, the block portion being screwed into the vinyl sill and header and the wooden frame members, the hardware with the carriers and interconnected pivots are then installed with the sash and squared in position.

73. The kit of claim 72 wherein the window sash includes a central locking handle and racks and pinions contained in the sash adjacent the opening end and contains the interconnecting shaft for the pivots adjacent the pivoting end.

5

74. A method of assembling a window sash, said window sash being used with a casement, tilt and slide or double-hung window and being interchangeable and of standard construction with respect to the various window sashes required, said method comprising:

10

- (1) forming the sash element according to the standard profile, said standard profile comprising a generally rectangular "I" shaped member having a center reinforcement comprising an inner and an outer wall and a hollow therebetween and having extending from the ends of these inner and outer walls proximate both the top and bottom thereof substantially "I" shaped members extending substantially horizontally in profile extending along the length of the sash element also having inner and outer walls and a hollow therebetween, the sash element having provided proximate one end thereof flanges extending inwardly toward one another for receiving a dust cover or auxiliary member fastening thereto and having located proximate the other end thereof a glass engaging recess, the cover or auxiliary member being fastened to the sash profile and being variable from window style to window style,
- (2) inserting the glass within the glass receiving portion of the sash elements and,
- (3) connecting said sash elements with interior corner connectors having a quick fastening feature which are inserted within the central opening of the sash profiles provided and provide a one-way friction fit engaging the opening of the centre portion of said sash profile for connecting the corners proximate the interior of the sash element

15

20

25

30

35

- 64 -

wherein said sash may be used for a tilt and slide window, double-hung window, or casement windows.

75. A method of assembling a window of claim 49, 50, 51, or
5 66 is provided comprising, the sash components being assembled
around a typical sealed double pane window glass by the quick
fastening feature of the corner locking portions which are inserted
within the opening of the sash profiles provided and providing one-
way friction fit, closed cell caulking is therefore inserted within the
10 top and bottom of the sash assembled and these portions are
covered by track covers by the compression of the closed cell foam
and the engagement of the tabs of the track cover with the tabs of
the sash profile, the hardware is then installed along the vertical
portions of the sash within the openings thereof opposite the glass
15 which is then covered by a sash cover portion provided, the
hardware located proximate the pivoting end is therefore installed
on the carrier portions and inserted within the track portion within
the sill and header, for example of a window assembly, wherein the
window is therefore closed in position with the sash covers or track
20 covers located proximate the sill and header snapping into the
frame and closing any path for air to enter the window and pass the
primary seals provided, the track covers also provide blockage of
light, air and the friction fit of the sash into the track portions.

25 76. The assembly of claim 49, 50, or 51 further comprising a
straight line window frame and assembly having a center mullion
wherein casement windows are disposed on each side of the
mullion with the operating portions including the carrier and
interconnected pivot assembly and shafts thereof, thereby
30 providing a double-casement window, wherein said casement
windows pivot in substantially opposite directions, and provide a
straight-line window when in the closed position.

77. The assembly of claim 49, 50, or 51 further comprising a
35 cover for a tilt and slide window track, the track comprising a first
half and a second half interconnected to provide a continuous track
for the window, the first half being disposed below the closed

- 65 -

window, and the second half being provided as a continuation of the first half, the second half including a track cover portion which clips into position to engage flange portions of a sill of the window and thereby provide support for the window as it glides along the
5 second half of the track.

1/24




FIG.1.

SUBSTITUTE SHEET

2 / 24




FIG.1A.

SUBSTITUTE SHEET

3 / 24




FIG. 1B.

SUBSTITUTE SHEET

4/24




FIG. 1C.

SUBSTITUTE SHEET




FIG.1D.

6 / 24




FIG. 2.

7 / 24




FIG. 2A.




FIG. 2B.

8 / 24




FIG. 3.

SUBSTITUTE SHEET

9/24




FIG. 4.





FIG. 5.

10 / 24



SUBSTITUTE SHEET

11 / 24





FIG. 7.

SUBSTITUTE SHEET



13/24




FIG. 9.

SUBSTITUTE SHEET

14/24





FIG.10.

15/24



SUBSTITUTE SHEET

16/24




FIG.12.

SUBSTITUTE SHEET

17 / 24




FIG.13 A.

SUBSTITUTE SHEET

18/24




FIG. 13B.




FIG. 13C.




FIG. 13.

19 / 24




FIG. 14.




FIG. 14 A.




FIG.15.

SUBSTITUTE SHEET




FIG. 16B.




FIG. 16A.




FIG. 16.





FIG.17.



SUBSTITUTE SHEET